

VT360

COMPACT LOADERS





		METRIC
CAPACITIES	Operating Weight	5516 kg
	Unladen weight	5032 kg
	Operating Capacity at 35% Tipping Load	1633 kg
	Operating Capacity At 50% Tipping Load	2332.82 kg
	Operating capacity at 35% tipping load with counterweight	1700.97 kg
Tipping capacity	4666 kg	
WEIGHT AND DIMENSIONS	Wheelbase	1702 mm
	Overall Operating Height - Fully Raised	4422 mm
	Height to Hinge Pin - Fully Raised	3442 mm
	Reach - Fully Raised	930 mm
	Dump angle at full height	41 °
	Dump Height - Fully Raised	2667 mm
	Overall Height to top of ROPS	2121 mm
	Overall length with bucket	3968 mm
	Overall Length without Bucket	3173 mm
	Specified Height	2563 mm
	Reach at Specified Height	978 mm
	Ground clearance	241 mm
	Crawler base	1702 mm
	Overall width less bucket	2032 mm
Bucket Width	2134 mm	
Clearance Radius - Front with Bucket	2426 mm	
PERFORMANCES	Ground Speed - Single Speed	10 km/h
	Ground Speed - Two Speed	14.80 km/h
ENGINE	Engine brand	Deutz
	Engine model	TCD3.6
	Engine power (Hp)	114 Hp
	Engine power (kW)	85 kW
HYDRAULICS	Standard flow - Auxiliary hydraulics	94.60 l/min
	High-Flow Auxiliary Hydraulics - Option	151.40 l/min
TANK CAPACITIES	Hydraulic tank capacity	27 l
	Fuel	143.80 l

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT